



The release system is protected with lock

The cable's horizontal outlet eases installation near the ground

Aluminium body with a double coat of paint for a longer life

## OPERATOR FOR SWING GATES

- Float bracket (out of axis thrust)
- Available versions: 230V and 24V
- It moves leaves up to 2,5m
- G-WAY system in 24V version (with Brain 15 Control Board) or in 230V version (with Brain 17 Control Board)
- PROcoder Safety System (with Brain 17 Control Board)
- Release through a user friendly accessory lever and customised key
- Sturdy inner kinematic mechanism made of a bronze crown and steel worm-screw
- Opening and closing slow down available in both versions
- Up to 30 consecutive cycles, 100 daily cycles
- Electric limit switches version (no need of opening and closing slow down)
- Horizontal output cables (installation closed to floor)
- Double painting layer

Code	Name	Version	Voltage	Leaf max. length	Use
6170124	Sirocco 250	Non-reversible	230V	2,5 m.	Residential / condominium
6170125	Sirocco 250 LS	Non-reversible / limit-switches	230V	2,5 m.	Residential / condominium
6170126	Sirocco 2524	Non-reversible	24V	2,5 m.	Residential / condominium
6170127	Sirocco 2524 LS	Non-reversible / limit-switches	24V	2,5 m.	Residential / condominium

## OPERATOR DIMENSIONS



Technical Specifications	Sirocco 250	Sirocco 250 LS	Sirocco 2524	Sirocco 2524 LS
Power supply (V)	230		24	
Nominal power (W)	250		70	
Current (A)	1.1		3	
Heat protection (°C)	140		-	
Thrust capacitor (µF)	6.3		-	
Thrust (daN)	200		250	
Travel (mm)	300 (350 mm without mechanical stops)			
Max. Speed (cm/sec.)	1.6			
Frequency of use at 20 °C	S3 - 30%	S3 - 35%	continuous	
Operating ambient temperature (°C)	-20 +55			
Protection class	IP54			
Weight (kg)	6,5			

## CONTROL BOARDS

Brain 592  
Brain 17  
Brain 15